

Mirror Type	Face Type	Order Code	Description	Fixing	Bracket Type	Distance Guide*
Premium Indoor						
800	Acrylic	6180	800mm Round	Wall or 60mm post	5	To 25m
600	Acrylic	6170	600mm Round	Wall or 60mm post	5	To 20m
450	Acrylic	6160	450mm Round	Wall or 60mm post	4	To 15m
300	Acrylic	6150	300mm Round	Wall or 60mm post	3	To 8m

Standard Indoor						
760	Acrylic	6270	760mm Round	Wall or Ceiling	2	Over 12m
600	Acrylic	6260	600mm Round	Wall or Ceiling	2	To 12m
450	Acrylic	6250	450mm Round	Wall or Ceiling	2	To 8m
300	Acrylic	6245	300mm Round	Wall or Ceiling	2	To 6m

Economy Indoor						
760	Acrylic	6373	760mm Round	Wall or Ceiling	1	Over 12m
600	Acrylic	6370	600mm Round	Wall or Ceiling	1	To 12m
450	Acrylic	6372	450mm Round	Wall or Ceiling	1	To 8m
300	Acrylic	6374	300mm Round	Wall or Ceiling	1	To 6m
305	Acrylic	6375	300 x 500mm Rectangular	Wall or Ceiling	1	To 8m

Domes Indoor						
Viewing distance measured viewer to mirror only.						
D-900	Acrylic	6398	Full Dome 900mm	Ceiling	Direct to ceiling	To 10m
D-600	Acrylic	6397	Full Dome 600mm	Ceiling	Direct to ceiling	To 5m
D-450	Acrylic	6393	Half Dome 900 x 450mm	Wall	Direct to wall	To 10m
D-360	Acrylic	6392	Half Dome 600 x 300mm	Wall	Direct to wall	To 5m
D450BK	Acrylic	6393BK	Half Dome 900 x 450mm	Wall or Pallet racking	1	To 10m
D-270	Acrylic	6394	Corner Dome 450 x 450 mm	Corner	Direct to corner	To 10m
D-180	Acrylic	6395	Corner Dome 300 x 300mm	Corner	Direct to corner	To 5m

Premium Outdoor						
SS-1000	Stainless Steel	6424P	1060mm Round with Visor	50, 60 or 76mm Post	7 or opt. 6	See note 1.
SS-800	Stainless Steel	6422P	840mm Round with Visor	50, 60 or 76mm Post	7 or opt. 6	See note 1.
SS-600	Stainless Steel	6421P	630mm Round with Visor	50, 60 or 76mm Post	7 or opt. 6	See note 1.
SS-655	Stainless Steel	6423P	650 x 500mm Rectangular	50, 60 or 76mm Post	7 or opt. 6	See note 1.
SS-450	Stainless Steel	6418	470mm Round	Wall or 60mm Post	4	To 20m
SS-300	Stainless Steel	6419	310mm Round	Wall or 60mm Post	3	To 15m
SS-23	Stainless Steel	6420	230 x 320mm Rectangular	Wall or 60mm Post	3	To 12m

Standard Outdoor						
X-1000	Acrylic	6495P	1000mm Round with Visor	50, 60 or 76mm Post	7 or opt. 6	See note 1.
X-800	Acrylic	6490P	800mm Round with Visor	50, 60 or 76mm Post	7 or opt. 6	See note 1.
X-600	Acrylic	6485P	600mm Round with Visor	50, 60 or 76mm Post	7 or opt. 6	See note 1.

Economy Outdoor						
B-1000	Acrylic	6360W	1000mm Round	Wall	6 or 7 at extra cost	Over 25m
B-800	Acrylic	6355W	800mm Round	Wall	6 or 7 at extra cost	To 25m
B-600	Acrylic	6350W	600mm Round	Wall	6 or 7 at extra cost	To 20m
B-655	Acrylic	6365W	650 x 500mm Rectangular	Wall	6 or 7 at extra cost	To 20m
B-450	Acrylic	6340	450mm Round	Wall	6 or 7 at extra cost	To 15m
B-300	Acrylic	6330	300mm Round	Wall	2	To 8m

Specifications subject to change without notice

Best Distance*	Measured by adding the distance from viewer to mirror, and mirror to subject being viewed. Distances are an indication only – most mirrors provide satisfactory service well beyond this range.
Note 1	Distance guide for traffic mirrors depends on the need to be noticed, area coverage required and the speed of the traffic. A larger mirror helps reduce reaction time.
Domes	Measured viewer to mirror only.